

## Heavy Duty Dock Hose – Petroleum Service



Series EW339

Custom Made Hose

Series EW339 is a heavy duty oil suction and discharge (OS&D)/dock hose for transferring oil between tankers, barges, and storage tanks. The hose construction incorporates a specially formulated tube that resists media to 50% aromatic content. The wire helix provides full suction capability, kink resistance and a path to conduct a static electrical charge to ground. The rugged cover is resistant to abrasion, mild chemicals, oil and weathering. Series EW339 meets all United States Coast Guard (USCG) requirements for dock/OS&D hose.

**NOTES:** • Other customized versions of this product are available. Contact Parker.

• For corrugated construction, refer to Series EWC439.

Tube: Black nitrile

Reinforcement: Multiple plies of tire cord with wire helix Cover: Black synthetic rubber; wrapped finish Temp. Range: -40°F to +180°F (-40°C to +82°C)

Brand Method: Black text on red stripe

Brand Example: PARKER SERIES EW339 NITRILE / OIL SERVICE

**Design Factor:** 4:1 **Industry Standards:** USCG

**Applications:** • Oil and fuel to 50% aromatic content

• Transfer between barges, storage tanks and marine vessels

**Vacuum:** 29" Hg (737 mm Hg)

**Couplings:** Built-in nipples, male pipe or flanged. Other configurations available.

Contact Parker.

#	0							$\mathcal{A}_{*}$		$\bigcirc$		$\Longrightarrow$
Part Number	ID (in)	ID (mm)	Reinf Layers	OD (in)	OD (mm)	Approx Wt (lbs/ft)	Approx Wt (kg/m)	Min Bend Rad (in)	Min Bend Rad (mm)	Max WP (psi)	Max WP (bar)	Max Lg (ft)
EW339-6000	6	152.4	4	7.1	181.0	8.00	5.41	36	914	200	14	50
EW339-8000	8	203.2	6	9.4	247.7	13.30	19.82	48	1219	200	14	50
EW339-10000	10	254.0	8	11.8	298.5	20.00	29.80	60	1524	200	14	50
EW339-12000	12	304.8	8	13.8	349.3	27.00	40.23	72	1829	200	14	50

WARNING: This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.